

# Link-Seal BC, BS316

Link chains for plastic pipes

**PRESSING WATER**

- Sealing of duct systems
- Installation in **pre-installed pipe sleeve** or **core bore in waterproof concrete** (white tank)
- **Split version**, for **pipes and cables that are already installed**



## PRODUCT ADVANTAGES

- Especially suitable for plastic pipes
- Quick installation thanks to pre-assembled system
- Robust rubber parts ensure a long service life
- The radial expansion of the rubber parts ensures a permanent, pressure-tight and secure sealing of the annular space
- Easy installation; even retrofitting possible

## TECHNICAL DETAILS


- Leak-tight against pressing water
- For galvanised screws: general application in normal atmosphere, water or humidity. Suitable for electrical insulation and cathodic corrosion protection
- F or stainless steel screws: high resistance to water, against most inorganic substances (acids and alkalis) and most organic substances (e.g. acetic acid and acetone)
- LS 200 to LS 275 FHRK standard 20, 30, 40
- LS 300 to LS 700 FHRK standard 20, 30, 40, 60

## MATERIAL

- Pressure plates: glass fibre reinforced polyamide
- Rubber material: softer EPDM rubber in blue (EPDM  $40^\circ \pm 5^\circ$  Shore A)
- Version BC: galvanised steel screws
- Version BS316: A4-70 stainless steel screws



Individual module



The HKD range is excluded from the DOYMA 25-year warranty.

### Link-Seal BC (galvanised steel screws)

Module type/ quantity	Inner diameter [DN in mm]	Outer diameter d [mm]	Article number
LS200	–	–	6 50 0 200 000 0 4
LS265	–	–	6 50 0 265 000 0 4
LS275	–	–	6 50 0 275 000 0 4
LS300	–	–	6 50 0 300 000 0 4
LS310	–	–	6 50 0 310 000 0 4
LS315	–	–	6 50 0 315 000 0 4
LS325	–	–	6 50 0 325 000 0 4
LS340	–	–	6 50 0 340 000 0 4
LS360	–	–	6 50 0 360 000 0 4
LS400	–	–	6 50 0 400 000 0 4
LS410	–	–	6 50 0 410 000 0 4
LS425	–	–	6 50 0 425 000 0 4
LS440*	–	–	6 50 0 440 000 0 0
LS475	–	–	6 50 0 475 000 0 4
LS500	–	–	6 50 0 500 000 0 4
LS525	–	–	6 50 0 525 000 0 4
LS575	–	–	6 50 0 575 000 0 4
LS625	–	–	6 50 0 625 000 0 4
LS650	–	–	6 50 0 650 000 0 4
LS700	–	–	6 50 0 700 000 0 4
7x275	80	40	6 50 0 040 080 0 4
5x340	100	32 + 40	6 50 0 040 100 0 4
6x315	100	50	6 50 0 050 100 0 4
7x340	125	63	6 50 0 063 125 0 4
8x315	125	75	6 50 0 075 125 0 4
5x410	150	63	6 50 0 063 150 0 4
9x340	150	90	6 50 0 090 150 0 4
7x310	150	110	6 50 0 110 150 0 4
7x475	200	110	6 50 0 110 200 0 4
9x360	200	125	6 50 0 125 200 0 4
13x340	200	140	6 50 0 140 200 0 4

### Link-Seal BS316 (A4-70 stainless steel screws)

Module type/ quantity	Inner diameter [DN in mm]	Outer diameter d [mm]	Article number
LS200	–	–	6 50 0 200 000 4 4
LS265	–	–	6 50 0 265 000 4 4
LS275	–	–	6 50 0 275 000 4 4
LS300	–	–	6 50 0 300 000 4 4
LS310	–	–	6 50 0 310 000 4 4
LS315	–	–	6 50 0 315 000 4 4
LS325	–	–	6 50 0 325 000 4 4
LS340	–	–	6 50 0 340 000 4 4
LS360	–	–	6 50 0 360 000 4 4
LS400	–	–	6 50 0 400 000 4 4
LS410	–	–	6 50 0 410 000 4 4
LS425	–	–	6 50 0 425 000 4 4
LS440*	–	–	6 50 0 440 000 4 0
LS475	–	–	6 50 0 475 000 4 4
LS500	–	–	6 50 0 500 000 4 4
LS525	–	–	6 50 0 525 000 4 4
LS575	–	–	6 50 0 575 000 4 4
LS625	–	–	6 50 0 625 000 4 4
LS650	–	–	6 50 0 650 000 4 4
LS700	–	–	6 50 0 700 000 4 4
7x275	80	40	6 50 0 040 080 4 4
5x340	100	32 + 40	6 50 0 040 100 4 4
6x315	100	50	6 50 0 050 100 4 4
7x340	125	63	6 50 0 063 125 4 4
8x315	125	75	6 50 0 075 125 4 4
5x410	150	63	6 50 0 063 150 4 4
9x340	150	90	6 50 0 090 150 4 4
7x310	150	110	6 50 0 110 150 4 4
7x475	200	110	6 50 0 110 200 4 4
9x360	200	125	6 50 0 125 200 4 4
13x340	200	140	6 50 0 140 200 4 4

Further material combinations available upon request. / \*black rubber