




Przekładnik prądowy z otworem na szynę i przewód - rozliczeniowy ASK 63.6

Prąd wtórny [A] / Klasa dokładności

Prąd pierwotny [A]	Moc przekładnika [VA]	Prąd wtórny [A] / Klasa dokładności				
		5 A Kl. 0,5 Nr katalogowy	5 A Kl. 0,5s Nr katalogowy	5 A Kl. 0,2 Nr katalogowy	1 A Kl. 0,5 Nr katalogowy	1 A Kl. 0,2 Nr katalogowy
250	2,5	G85558	G85602	G85513	G85758	G85713
	5	G85559	G85603		G85759	
300	2,5	G85560	G85604	G85515	G85760	G85715
	5	G85561	G85605	G85516	G85761	G85716
	10	G85562	G85606		G85762	
400	2,5	G85563	G85607	G85518	G85763	G85718
	5	G85564	G85608	G85519	G85764	G85719
	10	G85565	G85609		G85765	
500	2,5	G85566	G85610	G85521	G85766	G85721
	5	G85567	G85611	G85522	G85767	G85722
	10	G85568	G85612	G85523	G85768	G85723
	15	G85569	G85613		G85769	
600	2,5	G85570	G85614	G85525	G85770	G85725
	5	G85571	G85615	G85526	G85771	G85726
	10	G85572	G85616	G85527	G85772	G85727
	15	G85573	G85617	G85528	G85773	G85728
750	5	G85574	G85618	G85530	G85774	G85730
	10	G85575	G85619	G85531	G85775	G85731
	15	G85576	G85620	G85532	G85776	G85732
	30	G85577	G85621		G85777	
1000	5	G85578	G85622	G85534	G85778	G85734
	10	G85579	G85623	G85535	G85779	G85735
	15	G85580	G85624	G85536	G85780	G85736
	30	G85581	G85625		G85781	
1200	5	G85582	G85626	G85538	G85782	G85738
	10	G85583	G85627	G85539	G85783	G85739
	15	G85584	G85628	G85540	G85784	G85740
	30	G85585	G85629		G85785	
1250	5	G85586	G85630	G85542	G85786	G85742
	10	G85587	G85631	G85543	G85787	G85743
	15	G85588	G85632	G85544	G85788	G85744
	30	G85589	G85633		G85789	
1500	5	G85590	G85634	G85546	G85790	G85746
	10	G85591	G85635	G85547	G85791	G85747
	15	G85592	G85636	G85548	G85792	G85748
	30	G85593	G85637		G85793	



Szyna 1 60 x 30 mm
 Max. średnica przewodu 30 mm
 Szerokość 88 mm
 Wysokość 132 mm
 Głębokość 78 mm



Nr katalogowy



Uchwyt do montażu na szynę DIN 35 mm

-



Ośłona do plombowania Forma C

59042