


Articolo/Type
Descrizione/Description

BM 5341

Per capicorda preisolati da 0,25 a 6 mm² (AWG 22-10)
For insulated terminals 0,25-6 mm² (AWG 22-10)




BM 5371

Per terminali a bussola da 0,5 a 4 mm² (AWG 22-12)
For end sleeves terminals 0,5-4 mm² (AWG 22-12)




BM 5391

Per terminali a bussola da 6 a 16 mm² (AWG 10-6)
For end sleeves terminals 6-16 mm² (AWG 10-6)



BM 5331

Per terminali a bussola da 25 a 50 mm² (AWG 4-1)
For end-sleeves terminals 25-50 mm² (AWG 4-1)



BM 5313

Per capicorda in ottone aperti da 0,5 a 6 mm² (AWG 20-10)
For barrel open terminals 0,5-6 mm² (AWG 20-10)



BM 5314

Per femmina 90° - 1 mm² (AWG 18)
For 90° female terminal 1 mm² (AWG 18)



BM 5315

Per femmina 90° - 2,5 mm² (AWG 14)
For 90° female terminal 2,5 mm² (AWG 14)



BM 5351

Per capicorda non isolati rame da 0,5 a 10 mm² (AWG 20-8)
For uninsulated copper terminals 0,5-10 mm² (AWG 20-8)



BM 5431

Per connettori coassiali RG58-59
For coaxial connectors RG58-59

